

FEATURES:

- Plug and play fiber solution eliminates in-field termination and fusion splice, reduces installation cost and time
- Fits all standard 19 inch racks, height / port number: 1U / 96 Ports
- Suitable for four 2x12 module (P/N 247000122)
- Material/thickness of body and adapter panels: cold rolled steel
- TIA/EIA 568-B.3 standard
- RoHS compliant



(This FO panel doesn't include any adapters, patch cords or modules)

APPLICATIONS:

- Data center
- Telecommunications
- Local Area Network
- FTTH deployments
- Data communication network
- CATV
- Provide termination, protection, connection, management of fiber optic cable

SPECIFICATION:

- Constructed of base 1.2mm SPCC and cover 1.0mm SPCC
- Metallic surface with liquid coating and color black(RAL9005)

Premium Line Systems GmbH reserves the right to change specifications without prior notice.

PERFORMANCE:

- Operating Temperature -20° to + 70°
- Storage Temperature -40° to +80°

ORDERING INFORMATION:

Part No.	246104962
Description	Premium Line 19" 1U fiber optic patch panel, 96 ports, main body, black
Packing	1pc/box, 6pcs/carton
Carton dimension	52 x 35 x 26 cm, Weight: G.W. 19.8 kg N.W. 18.1 kg

Premium-Line Systems GmbH, Rosenheimer Str.89, D-83064 Raubling, Germany

► TEL: + 49(0)8035 9836 0 ► Fax: + 49(0)8035 9836 22

Premium Line Systems GmbH reserves the right to change specifications without prior notice.