

FEATURES:

- meets TEA/EIA 568-B.3 FOCIS-3 standard
- zirconia ferrule
- all connectors with dust cap
- color code: single mode (blue) and multimode (beige)
- boot for 3.0mm, 2.0mm and 900um cable diameter are available.
- RoHS compliant



APPLICATIONS:

- Telecommunication and CATV
- LAN (including FITL, FTTH and FTTD) and Data network

SPECIFICATIOIS:

	Conditions	Values
Insertion Loss(SM)	Against Reference Connector	<0.2dB
Insertion Loss(MM)	Against Reference Connector	<0.35dB
Return Loss(SM)	Against Reference Connector	>50dB
Durability	1000times	<0.2dB
Impact	1.5mm drop, 8 times	<0.2dB
Temperature Cycle	- 40°C~80°C, Du ring 5 cycles	<0.2dB
Operating Temperature	-20°C to +70°C	

ORDERING INFORMATION:

Part No. 232x20y5z
 Description: Fiber optic bulk connector, 3.0mm
 x, mode 1:MM 2:SM
 y, connector* 1:SC/PC 2: ST/PC 4: LC/PC 5:MTRJ/PC
 z, color 4:blue 8:beige
 Packing 1 pc/PE bag, 100 pcs/PE bag, 1000 pcs/carton
 Carton dimension: 29.2 x 21.2 x 21 cm, Weight: N.W.6.2KG G.W 7.3KG

**UPC or APC type connector upon customer request*

Premium-Line Systems GmbH, Rosenheimer Str.89, D-83064 Raubling, Germany

► TEL: + 49(0)8035 9836 0 ► Fax: + 49(0)8035 9836 22

Premium Line Systems GmbH reserves the right to change specifications without prior notice.