

Description:

Field assembly connector is very easy installable and re-usable field assembly connector which the fiber can be connected/disconnected only by on/off of a small latch attached on connector body, which is composed of two parts of a connector body and a boot it is designed to have the structure and the function to construct the more economic FTTH network.



Features:

- No need to use special Jig for assembling
- Can be reusable about 10 times
- Various cable can be acceptable with one type FAC (Ø250-900µm, 1.6x2.0mm, 2.0x3.0mm, 3.0mm)

Compliances:

- GR-326-CORE

Applications:

- FTTH end user termination
- Patch panels
- Rapid repair of optical networks
- Direct equipment termination

Specification:

Item	Data
Fiber Polishing Method	SPC Polish, APC Polish
Applicable fiber	Ø 250-900µm, 1.6x2.0, 2.0x3.0, Ø3.0mm(SM, MM50, MM62.5,
Insertion Loss	Typ. ≤0.3 dB / Max. ≤0.5 dB
Return Loss	>45dB (SM fiber SPC polish) >50dB (SM fiber APC polish / When use with Flat cleaver) >65dB (SM fiber APC polish / When use with Angled cleaver)
Operational Temperature	-40 - +85°
Pull test	<0.2dB, 4N load(0.125 fiber) < 0.2dB, 40N load (2x3mm, Ø 3.0mm)
Impact test	< 0.2dB, 1.5m, 10 repetitions
Durability test	< 0.2dB, 200 repetition of connecting/disconnecting
Vibrate test	< 0.2dB, 3 axes 2hr/axis, 1.5mm(peak-peak), 10 to
Thermal Cycle test	< 0.2dB, -40 to 75 °C, 21 cycles for 168 hours(3.0mm cable)
humidity test	< 0.2dB, 90 to 95%RH, Temp75°C for 168hrs

ORDERING INFORMATION:

Part No. 236x20yzw
 Description: Premium Line Field Assembly Connector
 x, mode 1:MM 2:SM
 y, connector 1:SC/APC 4:LC/APC 6:SC/UPC 9:LC/UPC
 z, diameter 3: 0.9mm(only for LC) 4: 2.0mm(only for SC) 5: 3.0mm(only for SC)
 w, color 1:white 4:blue 6:green
 Packing 50 pcs/PE bag, 2000 pcs/box
 Carton dimension: 33 x 33 x 28 cm, Weight: N.W.6KG G.W 6.4KG

Premium-Line Systems GmbH, Rosenheimer Str.89, D-83064 Raubling, Germany

► TEL: + 49(0)8035 9836 0 ► Fax: + 49(0)8035 9836 22